WUXI SUNKING INT'L TRADING CO., LTD SUNKING (WUXI) CABLE MATERIALS CO., LTD SUNKING (WUXI) TAPE & FOIL PRODUCTS CO., LTD

Tel: +86 510 89995648, 82715648 Fax: +86 510 82715648 Mob: +86 13771061594

ALUMINIUM TAPE FOR ARMOURING

1. Application:

The Aluminum Tape described in this sheet is mainly used as armouring of power cables and applied helically upon the bedded cables as a mechanical protection.

2. Standards:

It follows the latest standards of GB, IEC and DIN.

3. Requirements:

3.1 Size:

Aluminum tape shall be of the following dimensions and tolerances:

Alloy: 1100, 1200, 8011 etc

Thcikness(+/-0.02mm): 0.10mm, 0.15mm, 0.20mm, 0.30mm, 0.50mm etc

Width(+/-0.1mm): as specified by buyer's purchase order

ID(+/-1mm): 76mm, 102mm, 150mm, 300mm etc

OD(+/-10mm): max. 900mm

3.2 Mechanical Properties:

Elongation: min.15%

Tensile Strength: min. 70 MPa

Aluminum alloy: 99.5%

4. Finishing and Appearance:

Aluminum tape is of uniform quality and in continuous length without any joints. The appearance is clean, smooth, without any sharp edges, oils and other defects.

5. Packing and Marking:

As specified by buyer's purchase order, export standard seaworthy packing for long ocean transportation.

6. Testing:

Testing certificates will be attached along with each lot of shipment from suppliers.